

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY
DIESEL SAE 5W-40
ENGINE OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A
Skin sensitization : Category 1
Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms :  

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.

Precautionary Statements : If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.

ASHLAND®		Page: 2
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HEAVY PARAFFINIC DISTILLATE	64742-54-7	Asp. Tox. 1; H304	46.04
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411	2.19

ASHLAND®		Page: 3
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

TETRAPROPENYLPHENOL	121158-58-5	Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.19
---------------------	-------------	---	------

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
If swallowed	: Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

ASHLAND®		Page: 4
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO₂)

Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
hydrogen sulfide
metal oxides
nitrogen oxides (NO_x)
sulfur oxides

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : Use personal protective equipment.

ASHLAND®		Page: 5
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

protective equipment and emergency procedures	Ensure adequate ventilation. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours/dust. Do not smoke. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Container hazardous when empty. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures	: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
-----------------------------	--

ASHLAND®		Page: 6
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Personal protective equipment

Respiratory protection	: In the case of vapour formation use a respirator with an approved filter.
	A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.
Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
Skin and body protection	: Wear as appropriate: impervious clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures	: Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
	: No data available
Boiling point/boiling range	: 392 °F / 200 °C Calculated Phase Transition Liquid/Gas
Flash point	: > 390 °F / > 199 °C

ASHLAND®		Page: 7
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) GLP: Calculated Explosive Limit
Lower explosion limit	: 1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 1.3333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.8556 (20 °C)
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 100 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents

ASHLAND®		Page: 8
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Hazardous decomposition
products

carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD 50 (Rat): > 15 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg

ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity : LD 50 (Rat): > 2,000 - 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal
absorption under GHS.

TETRAPROPENYLPHENOL:

Acute oral toxicity :
Assessment: The component/mixture is classified as acute
oral toxicity, category 5.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Irritating to skin

TETRAPROPENYLPHENOL:

Result: Irritating to skin

ASHLAND®		Page: 9
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Not irritating to eyes

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Corrosive to eyes

TETRAPROPENYLPHENOL:

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

TETRAPROPENYLPHENOL:

Reproductive toxicity - : Some evidence of adverse effects on sexual function and
Assessment fertility, and/or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

ASHLAND®		Page: 10
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

HEAVY PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

TETRAPROPENYLPHENOL:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

ASHLAND®		Page: 11
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

ASHLAND®		Page: 12
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ARSENIC	7440-38-2	1	47619.047619

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	2.19 %
---------------------------------	------------	--------

ASHLAND®		Page: 13
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

ZINC COMPOUNDS Not Assigned 2.19 %

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	30.00 - 50.00 %
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	20.00 - 30.00 %
LUBRICANT ADDITIVE	Not Assigned	10.00 - 20.00 %
HYDROGENATED POLYDECENE	68037-01-4	10.00 - 20.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	5.00 - 10.00 %

New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	30.00 - 50.00 %
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	20.00 - 30.00 %
LUBRICANT ADDITIVE	Not Assigned	10.00 - 20.00 %
HYDROGENATED POLYDECENE	68037-01-4	10.00 - 20.00 %
HEAVY PARAFFINIC DISTILLATE	64742-54-7	5.00 - 10.00 %
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	1.00 - 5.00 %
ZINC COMPOUNDS	Not Assigned	1.00 - 5.00 %

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL.
AUSTR	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECL	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

ASHLAND®		Page: 14
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/02/2015

NFPA:	HMIS III:						
Flammability Health Instability Special hazard. 	<table border="1"> <tr> <td>HEALTH</td><td>2</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further information

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

ASHLAND®		Page: 15
SAFETY DATA SHEET		Revision Date: 06/02/2015
		Print Date: 1/13/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL		Version: 1.2
774038		

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System