



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 1: Identification

1.1 Product identifier

Trade name **POR-15 HIGH TEMPERATURE MANIFOLD GREY**
Product code(s) 44201, 44204, 44205, 44216, 44255

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Paint

1.3 Details of the supplier of the safety data sheet

P.O.R. Products
38 Portman Road
New Rochelle NY 10801
United States

Telephone: +1 914-636-0700
e-mail: support@porproducts.com
Website: www.porproducts.com

e-mail (competent person) support@porproducts.com

1.4 Emergency telephone number

Emergency information service 1-800-255-3924
ChemTel Inc.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.8	specific target organ toxicity - single exposure	1	STOT SE 1	H370
A.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311	If exposed: Call a poison center/doctor.
P308+P313	If exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

Naphtha (petroleum), hydrotreated heavy, 2-butan-one oxime, stoddard solvent, MINERAL SPIRITS 66/
1

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

2.3 Other hazards

Hazards not otherwise classified

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Manganese ferrite black spinel	CAS No 68186-94-7	50 – < 75	
Naphtha (petroleum), hydrotreated heavy	CAS No 64742-48-9	10 – < 25	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224
SCHLENK EM 90 (MS) SILVER		10 – < 25	
MINERAL SPIRITS 66/1	CAS No 64742-48-9	10 – < 25	Muta. 1B / H340 Carc. 1A / H350 Asp. Tox. 1 / H304
stoddard solvent	CAS No 8052-41-3	5 – < 10	Acute Tox. 3 / H331 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	CAS No 68953-58-2	1 – < 5	
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	1 – < 5	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
propan-2-ol	CAS No 67-63-0	1 – < 5	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-butanone oxime	CAS No 96-29-7	1 – < 5	Acute Tox. 3 / H301 Acute Tox. 4 / H312 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 Carc. 1B / H350 STOT SE 1 / H370 STOT SE 3 / H336 STOT RE 2 / H373 Flam. Liq. 4 / H227
2-ethylhexanoic acid, zirconium salt	CAS No 22464-99-9	0.1 – < 1	Acute Tox. 4 / H332
xylene	CAS No 1330-20-7	0.1 – < 1	Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	CAS No 136-52-7	0.1 – < 1	
ethyl benzene	CAS No 100-41-4	0.1 – < 1	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
2-methoxy-1-methylethyl acetate	CAS No 108-65-6	0.1 – < 1	Flam. Liq. 3 / H226
n-butyl acetate	CAS No 123-86-4	0.1 – < 1	STOT SE 3 / H336 Flam. Liq. 3 / H226
Crystalline silica (quartz)	CAS No 14808-60-7	0 – < 0.1	Carc. 1A / H350
2-(2-butoxyethoxy)ethanol	CAS No 112-34-5	0 – < 0.1	Eye Irrit. 2 / H319
naphthalene	CAS No 91-20-3	0 – < 0.1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351
benzene	CAS No 71-43-2	0 – < 0.1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225
toluene	CAS No 108-88-3	0 – < 0.1	Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225

For full text of abbreviations: see SECTION 16.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 4: First-aid measures**4.1 Description of first-aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/ OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							ACGIH® 2023
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1000
US	propylene glycol monomethyl ether acetate	108-65-6	PEL (CA)	100	541	150	811				Cal/ OSHA PEL
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							ACGIH® 2023
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1000
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500			Cal/ OSHA PEL



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Occupational exposure limit values (Workplace Exposure Limits)

Coun-try	Name of agent	CAS No	Identi-fier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Nota-tion	Source
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	ACGIH® 2023
US	n-butyl acetate	123-86-4	PEL (CA)	150	710	200	950				Cal/ OSHA PEL
US	n-butyl acetate	123-86-4	REL	150 (10 h)	710 (10 h)	200	950				NIOSH REL
US	n-butyl acetate	123-86-4	TLV®	50		150					ACGIH® 2023
US	n-butyl acetate	123-86-4	PEL	150	710						29 CFR 1910.1000
US	xylene, mixture of isomers	1330-20-7	TLV®	20							ACGIH® 2023
US	xylene, mixture of isomers	1330-20-7	PEL	100	435						29 CFR 1910.1000
US	xylene (dimethyl-benzene)	1330-20-7	PEL (CA)	100	435	150	655	300			Cal/ OSHA PEL
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	2-propanol	67-63-0	TLV®	200		400					ACGIH® 2023
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/ OSHA PEL
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOSH REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1000
US	benzene	71-43-2	PEL (CA)	1		5					Cal/ OSHA PEL



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Occupational exposure limit values (Workplace Exposure Limits)

Coun-try	Name of agent	CAS No	Identi-fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota-tion	Source
US	benzene	71-43-2	PEL	1		5					29 CFR 1910.1000
US	benzene	71-43-2	REL	0.1 (10 h)		1				appx-A	NIOSH REL
US	benzene	71-43-2	TLV®	0.5		2.5				H	ACGIH® 2023
US	benzene	71-43-2	PEL	10		50 (10 min)		25		us-pel-z2a	29 CFR 1910.1000
US	stoddard solvent	8052-41-3	PEL (CA)	100	525						Cal/ OSHA PEL
US	stoddard solvent	8052-41-3	REL		350 (10 h)				1,800 (15 min)		NIOSH REL
US	stoddard solvent	8052-41-3	TLV®	100							ACGIH® 2023
US	stoddard solvent	8052-41-3	PEL	500	2,900						29 CFR 1910.1000
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5						Cal/ OSHA PEL
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1000
US	naphthalene	91-20-3	TLV®	10						H	ACGIH® 2023

Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
Ceiling-C	ceiling value is a limit value above which exposure should not occur
H	absorbed through the skin
iv	inhalable fraction and vapor
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
us-pel-z2a	This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	ethylbenzene	mandelic acid, benzoylformic acid	crea	BEI®	0.15 g/g	ACGIH® 2023
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2023
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2023
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2023
US	xylene, mixture of isomers	methylhippuric acids	crea	BEI®	1.5 g/g	ACGIH® 2023
US	isopropanol	acetone		BEI®	40 mg/l	ACGIH® 2023
US	benzene	S-phenylmercapturic acid	crea	BEI®	25 µg/g	ACGIH® 2023
US	benzene	trans,trans-muconic acid	crea	BEI®	500 µg/g	ACGIH® 2023

Notation

crea creatinine
hydr hydrolysis

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Manganese ferrite black spinel	68186-94-7	DNEL	10 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
stoddard solvent	8052-41-3	DNEL	44 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
stoddard solvent	8052-41-3	DNEL	55 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
stoddard solvent	8052-41-3	DNEL	44 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
stoddard solvent	8052-41-3	DNEL	55 mg/m³	human, inhalatory	worker (industry)	acute - local effects
stoddard solvent	8052-41-3	DNEL	80 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
stoddard solvent	8052-41-3	DNEL	30 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
2-butanone oxime	96-29-7	DNEL	9 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	3.33 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
2-butanone oxime	96-29-7	DNEL	1.3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-butanone oxime	96-29-7	DNEL	2.5 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	DNEL	235.1 µg/m ³	human, inhalatory	worker (industry)	chronic - local effects
ethyl benzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethyl benzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethyl benzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-methoxy-1-methyl-ethyl acetate	108-65-6	DNEL	275 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-methoxy-1-methyl-ethyl acetate	108-65-6	DNEL	550 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-methoxy-1-methyl-ethyl acetate	108-65-6	DNEL	796 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	67.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	101.2 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
2-(2-butoxyethoxy)ethanol	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
toluene	108-88-3	DNEL	192 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
stoddard solvent	8052-41-3	PNEC	0.14 mg/l	aquatic organisms	freshwater	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	0.35 mg/l	aquatic organisms	marine water	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	1.14 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
stoddard solvent	8052-41-3	PNEC	0.14 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	0.256 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butanone oxime	96-29-7	PNEC	177 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	6.58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene	1330-20-7	PNEC	12.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	2.31 mg/kg	terrestrial organisms	soil	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	0.62 µg/l	aquatic organisms	freshwater	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	2.36 µg/l	aquatic organisms	marine water	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	0.37 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	53.8 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	69.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	PNEC	10.9 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethyl benzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
ethyl benzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethyl benzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethyl benzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.635 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.064 mg/l	aquatic organisms	marine water	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	3.29 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.329 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-methoxy-1-methyl-ethyl acetate	108-65-6	PNEC	0.29 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-(2-butoxyethoxy)ethanol	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
benzene	71-43-2	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
benzene	71-43-2	PNEC	39 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
benzene	71-43-2	PNEC	33 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
benzene	71-43-2	PNEC	4.8 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flash point	41.1 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	7.6 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solid content	71.75 %
---------------	---------

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
stoddard solvent	8052-41-3	inhalation: vapor	>5.5 mg/l/4h
Distillates (petroleum), hydro-treated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
2-butanone oxime	96-29-7	dermal	>1,000 mg/kg
2-butanone oxime	96-29-7	inhalation: vapor	>4.83 mg/l/4h
2-ethylhexanoic acid, zirconium salt	22464-99-9	inhalation: dust/mist	>4.3 mg/l/4h
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapor	11 mg/l/4h
ethyl benzene	100-41-4	inhalation: vapor	11 mg/l/4h
naphthalene	91-20-3	oral	710 mg/kg
naphthalene	91-20-3	inhalation: vapor	>0.4 mg/l/4h
naphthalene	91-20-3	inhalation: dust/mist	0.005 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
ethyl benzene	100-41-4	2B	
Crystalline silica (quartz)	14808-60-7	1	
propan-2-ol	67-63-0	3	
benzene	71-43-2	1	

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
naphthalene	91-20-3	2B	
toluene	108-88-3	3	
xylene	1330-20-7	3	

Legend

- 1 Carcinogenic to humans
- 2B Possibly carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
benzene	71-43-2	Known to be a human carcinogen	1st Report on Carcinogens
naphthalene	91-20-3	Reasonably anticipated to be a human carcinogen	11th Report on Carcinogens

29 CFR 1910/1915/1926 Occupational Safety and Health Standards: Toxic and Hazardous Substances (carcinogens)

Name of substance	CAS No	Type of registration
benzene	71-43-2	GI §1910.1028, SE §1915.1028, CI §1926.1128

Legend

- CI §1926.1128 Construction Industry (29 CFR 1926.1128)
- GI §1910.1028 General Industry (29 CFR 1910.1028)
- SE §1915.1028 Shipyard Employment (29 CFR 1915.1028)

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Causes damage to organs.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha (petroleum), hydrotreated heavy	64742-48-9	LL50	8.2 mg/l	fish	96 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	4.5 mg/l	aquatic invertebrates	48 h
stoddard solvent	8052-41-3	LC50	0.18 mg/l	fish	96 h
stoddard solvent	8052-41-3	LL50	41.4 mg/l	fish	96 h
stoddard solvent	8052-41-3	EL50	2.5 mg/l	algae	96 h
stoddard solvent	8052-41-3	EC50	0.58 mg/l	algae	96 h
Distillates (petroleum), hydro-treated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydro-treated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
2-butanone oxime	96-29-7	LC50	>100 mg/l	fish	96 h
2-butanone oxime	96-29-7	EC50	201 mg/l	aquatic invertebrates	48 h
2-butanone oxime	96-29-7	ErC50	11.8 mg/l	algae	72 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	LC50	>100 mg/l	fish	96 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	LL50	>100 mg/l	fish	96 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	EC50	>0.17 mg/l	aquatic invertebrates	48 h
2-ethylhexanoic acid, zirconium salt	22464-99-9	ErC50	49.3 mg/l	algae	72 h
xylene	1330-20-7	LC50	8.4 mg/l	fish	96 h
xylene	1330-20-7	EC50	4.9 mg/l	algae	72 h
xylene	1330-20-7	ErC50	4.7 mg/l	algae	72 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	LC50	54.1 mg/l	fish	96 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	EC50	2,618 µg/l	aquatic invertebrates	48 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	ErC50	71,314 µg/l	algae	96 h

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethyl benzene	100-41-4	LC50	7 mg/l	fish	24 h
ethyl benzene	100-41-4	EC50	2.4 mg/l	aquatic invertebrates	48 h
2-methoxy-1-methylethyl acetate	108-65-6	LC50	180 mg/l	fish	96 h
2-methoxy-1-methylethyl acetate	108-65-6	EC50	>500 mg/l	aquatic invertebrates	48 h
2-methoxy-1-methylethyl acetate	108-65-6	ErC50	>1,000 mg/l	algae	96 h
n-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	EC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h
2-(2-butoxyethoxy)ethanol	112-34-5	LC50	1,300 mg/l	fish	96 h
2-(2-butoxyethoxy)ethanol	112-34-5	EC50	>100 mg/l	aquatic invertebrates	48 h
2-(2-butoxyethoxy)ethanol	112-34-5	ErC50	>100 mg/l	algae	96 h
naphthalene	91-20-3	LC50	1.6 mg/l	fish	96 h
naphthalene	91-20-3	EC50	2.16 mg/l	aquatic invertebrates	48 h
toluene	108-88-3	LC50	5.5 mg/l	fish	96 h
toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h
benzene	71-43-2	LC50	5.3 mg/l	fish	96 h
benzene	71-43-2	EC50	10 mg/l	aquatic invertebrates	24 h
benzene	71-43-2	ErC50	100 mg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Manganese ferrite black spinel	68186-94-7	EC50	≥10,000 mg/l	microorganisms	3 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	10 mg/l	fish	21 d
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
stoddard solvent	8052-41-3	EL50	1.19 mg/l	aquatic invertebrates	21 d

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	8052-41-3	EC50	0.33 mg/l	aquatic invertebrates	21 d
Distillates (petroleum), hydro-treated light	64742-47-8	EL50	0.89 mg/l	aquatic invertebrates	21 d
2-butanone oxime	96-29-7	EC50	≥100 mg/l	aquatic invertebrates	21 d
2-ethylhexanoic acid, zirconium salt	22464-99-9	EC50	75 mg/l	aquatic invertebrates	21 d
xylene	1330-20-7	EL50	2.9 mg/l	aquatic invertebrates	21 d
xylene	1330-20-7	ErC50	4.36 mg/l	algae	73 h
xylene	1330-20-7	EC50	2.2 mg/l	algae	73 h
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	LC50	41,625 µg/l	fish	28 d
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	EC50	82.2 µg/l	aquatic invertebrates	21 d
ethyl benzene	100-41-4	LC50	3.6 mg/l	aquatic invertebrates	7 d
2-methoxy-1-methylethyl acetate	108-65-6	LC50	63.5 mg/l	fish	14 d
2-methoxy-1-methylethyl acetate	108-65-6	EC50	>100 mg/l	aquatic invertebrates	21 d
n-butyl acetate	123-86-4	EC50	34.2 mg/l	aquatic invertebrates	21 d
n-butyl acetate	123-86-4	LC50	43.5 mg/l	aquatic invertebrates	21 d
naphthalene	91-20-3	EC50	2.96 mg/l	algae	4 h
toluene	108-88-3	LC50	3.78 mg/l	aquatic invertebrates	2 d
toluene	108-88-3	EC50	3.23 mg/l	aquatic invertebrates	7 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263

14.2 UN proper shipping name

DOT	Paint
IMDG-Code	PAINT
ICAO-TI	Paint

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	stoddard solvent

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1263, Paint, 3, III, environmentally hazardous
Reportable quantity (RQ)	12,346 lbs (5,605 kg) (xylene) (ethyl benzene)
Danger label(s)	3, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	367, B1, B52, B131, IB3, T2, TP1, TP29
ERG No	128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	3, fish and tree



Special provisions (SP)	163, 223, 367, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	3



Special provisions (SP)	A3, A72, A192
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
ethyl benzene	100-41-4		1986-12-31
propan-2-ol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not required	1986-12-31
benzene	71-43-2		1986-12-31
naphthalene	91-20-3		1986-12-31
toluene	108-88-3		1986-12-31
xylene	1330-20-7		1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethyl benzene	100-41-4		1 2 3	1000 (454)
benzene	71-43-2	a	1 2 3 4	10 (4,54)
naphthalene	91-20-3		1 2 3 4	100 (45,4)
toluene	108-88-3		1 2 3 4	1000 (454)
xylene	1330-20-7		1 3 4	100 (45,4)
n-butyl acetate	123-86-4		1	5000 (2270)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)
- a Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Canada PBITs EC Annex VI CMRs - Cat. 1B
MINERAL SPIRITS 66/1	64742-48-9		Canada PBITs EC Annex VI CMRs - Cat. 1B
stoddard solvent	8052-41-3		ATSDR Neurotoxicants EC Annex VI CMRs - Cat. 1B
propan-2-ol	67-63-0		OEHHA RELs
2-butanone oxime	96-29-7		EC Annex VI CMRs - Cat. 1B
xylene	1330-20-7		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report IRIS Neurotoxicants OEHHA RELs
ethyl benzene	100-41-4		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IARC Carcinogens - 2B OEHHA RELs Prop 65
Crystalline silica (quartz)	14808-60-7		IARC Carcinogens - 1
2-(2-butoxyethoxy)ethanol			CA TACs
naphthalene	91-20-3		ATSDR Neurotoxicants CA NLs CA TACs CDC 4th National Exposure Report CWA 303(c) CWA 303(d) IARC Carcinogens - 2B IRIS Neurotoxicants NTP 13th RoC - reasonable OEHHA RELs Prop 65 U.S. EPA NWMP PBTs



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Name of substance	CAS No	Functionality	Authoritative Lists
benzene	71-43-2		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 1 IRIS Carcinogens - A NTP 13th RoC - known OEHHA RELs Prop 65
toluene	108-88-3		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) IRIS Neurotoxicants OEHHA RELs Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ethyl benzene	100-41-4				0.1 %
Crystalline silica (quartz)		1095			1.0 %
propan-2-ol	67-63-0				1.0 %
benzene	71-43-2				1.0 %
naphthalene	91-20-3				0.1 %
2-(2-butoxyethoxy)ethanol		1022			1.0 %
toluene	108-88-3				1.0 %
xylene	1330-20-7				1.0 %
n-butyl acetate	123-86-4		LHS		1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Naphtha (petroleum), hydrotreated heavy	64742-48-9	A, O	
propan-2-ol	67-63-0	A, N, O	
Manganese ferrite black spinel		A	dust
stoddard solvent	8052-41-3	A, N, O	
2-butanone oxime	96-29-7	I	
MINERAL SPIRITS 66/1	64742-48-9	A, O	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- dust If the substance poses an airborne particulate exposure hazard, the substance is followed by the word "dust."
- I American Industrial Hygiene Association (AIHA), "Workplace Environmental Exposure Level Guides" (1992), available from AIHA
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ethyl benzene	100-41-4		CA F3
Crystalline silica (quartz)	14808-60-7		CA
propan-2-ol	67-63-0		F3
benzene	71-43-2		CA MU F3
stoddard solvent	8052-41-3		F2
naphthalene	91-20-3		CA F2
2-(2-butoxyethoxy)ethanol			
toluene	108-88-3		TE F3
xylene	1330-20-7		F3
n-butyl acetate	123-86-4		F3

Legend

- CA Carcinogenic
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree
- MU Mutagenic
- TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
BENZENE, ETHYL-	100-41-4	E
2-PROPANOL	67-63-0	E
STODDARD SOLVENT	8052-41-3	
GLYCOL ETHERS		E
BENZENE, DIMETHYL-	1330-20-7	E
ACETIC ACID, BUTYL ESTER	123-86-4	E

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ethyl benzene	100-41-4	T, F
Crystalline silica (quartz)	14808-60-7	T
Crystalline silica (quartz)	14808-60-7	T
propan-2-ol	67-63-0	T, F
benzene	71-43-2	T, F, C
stoddard solvent	8052-41-3	T
naphthalene	91-20-3	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
toluene	108-88-3	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
xylene	1330-20-7	T, F
n-butyl acetate	123-86-4	T, F

Legend

C Carcinogenicity (IARC)
F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
naphthalene	91-20-3		cancer
toluene	108-88-3		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
US	TSCA	all ingredients are listed (ACTIVE)

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

POR-15 HIGH TEMPERATURE MANIFOLD GREY

Version number: GHS 2.0
Replaces version of: 2022-03-28 (GHS 1)

Revision: 2023-12-07

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.